



JGP150P1 / JGP165E1



GENSET MODEL

	Prime	JGP150P1	
	Standby	JGP165E1	
Engine speed	rpm	1500	1800
Frequency	Hz	50	60
Prime power	KVA	150	N/A
	KW	120	N/A
Standby power	KVA	165	N/A
	KW	132	N/A
Gross Engine Power	KW	151	N/A
	hp	202	N/A
* Ratings at 0.8 Power Factor			
Fuel consumption @50% load	L/hr	17.4	N/A
@75% load	L/hr	26.4	N/A
@100% load	L/hr	31.2	N/A

TECHNICAL DATA

Perkins Engine Model	1006TAG2	
Leroy Somer / Stamford Alternator Model	LSA44.2M95/UCI274F	
Number of Cylinders	6 in line	
Cubic Capacity	Litres	6
	cu.in	366
Bore	mm	100
	in	3.94
Stroke	mm	127
	in	5
Fuel Tank Capacity	Lit	275

DIMENSIONS & WEIGHT

Length	cm	270
Width	cm	90
Height	cm	147
weight	Kg	1535

Prime rating: These ratings are applicable for supplying continuous electrical power in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

Standby Rating: These ratings are applicable for supplying continuous electrical power in the event of utility power failure. No overload is permitted on these ratings

Headquarter
Jubaili Bldg,
Maarouf Saad Boulevard
P.O. Box 60, Sidon, Lebanon
Tel: +961 7 730871
www.JubailiBros.com

