




JGP1500P3 / JGP1650E3



GENSET MODEL

	Prime	JGP1500P3	
	Standby	JGP1650E3	
Engine speed	rpm	1500	1800
Frequency	Hz	50	60
Prime power	KVA KW	1500 1200	N/A N/A
Standby power	KVA KW	1650 1320	N/A N/A
Gross Engine Power	KW hp	1437 1927	N/A N/A

*Ratings at 0.8 Power Factor

Fuel consumption @50% load	L/hr	160	N/A
@75% load	L/hr	226	N/A
@100% load	L/hr	297	N/A

TECHNICAL DATA

Perkins Engine Model	4012-46TAG2A	
Leroy Somer Alternator Model	LSA50.2L8	
Number of Cylinders	12 / V Type	
Cubic Capacity	Litres	45.8
	cu.in	2797.5
Bore	mm	160
	in	6.3
Stroke	mm	190
	in	7.5
Fuel Tank Capacity	Lit	N/A

DIMENSIONS & WEIGHT

Length	cm	510
Width	cm	190
Height	cm	244
weight	Kg	9910

Prime rating: These ratings are applicable for supplying continuous electrical power in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours

Standby Rating: These ratings are applicable for supplying continuous electrical power (at variable load) in the event of utility power failure. No overload is permitted on these ratings

Headquarter
Jubaili Bldg,
Maarouf Saad Boulevard
P.O. Box 60, Sidon, Lebanon
Tel: +961 7 730871
www.JubailiBros.com

