



JGP180P2 / JGP200E2



GENSET MODEL

	Prime	JGP180P2	
	Standby	JGP200E2	
Engine speed	rpm	1500	1800
Frequency	Hz	50	60
Prime power	KVA	180	196.9
	KW	144	157.5
Standby power	KVA	200	218.8
	KW	160	175
Gross Engine Power	KW	180	204.3
	hp	242	274

*Ratings at 0.8 Power Factor

Fuel consumption	@50% load	L/hr	21.2	27.3
	@75% load	L/hr	30.9	35.4
	@100% load	L/hr	40	44.3

TECHNICAL DATA

Perkins Engine Model	1106C-E66TAG4		
Leroy Somer / Stamford Alternator Model	LSA46.2M3/UCI274G		
Number of Cylinders	6 in line		
Cubic Capacity	Litres	6.6	
	cu.in	402.8	
Bore	mm	105	
	in	4.1	
Stroke	mm	127	
	in	5	
Fuel Tank Capacity	Lit	275	

DIMENSIONS & WEIGHT

Length	cm	280
Width	cm	90
Height	cm	160
weight	Kg	1660

Prime rating: These ratings are applicable for supplying continuous electrical power in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

Standby Rating: These ratings are applicable for supplying continuous electrical power in the event of utility power failure. No overload is permitted on these ratings

Headquarter
Jubaili Bldg,
Maarouf Saad Boulevard
P.O. Box 60, Sidon, Lebanon
Tel: +961 7 730871
www.JubailiBros.com

