



MP53-MP59E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Output Rating at - 60Hz					
220/127V	KVA			KW	
Prime	53.	0		4	2.4
Standby	59.	0		4	7.2
					@ 0.8 p.f.
Generator Outp	out Rati	ng at -	60H	lz	
380/220V	KV	4		I	KW
Prime	46.0			3	6.8
Standby	51.0			4	0.8
					@ 0.8 p.f.
Engine Data					
Engine Manufact	urer:	F	Perkir	ns UK	
Engine Model:	1103A-33TG1				
Number of Cylind	f Cylinders: 3				
Cylinder Arrange	ment:	Ve	rtical	In Line	
Cycle:			4 Str	oke	
Bore/Stroke mm	(in):	105.0 (4	4.1) /	127.0	(5.0)
Induction:		Tu	rbo c	harged	
Compression rati	o:		17.2	:5:1	
Displacement / (c	u.in):		3.3 (2	201)	

General Data			
	Liter	US/Gal	
Fuel Tank Capacity:	220.0	58.1	
Fuel Tank:	UV Resistant MDPE		
Base Frame:	Heavy Duty-Powder Coated		
Control Panel:	Deep Sea Electronics		
Circuit Breaker:	ABB 3 Pole MCB		

Performance	60	HZ	
Engine Speed:	1800		
Gross Engine Power:	kWm	Bhp	
Prime:	50.5	67.7	
Standby:	54.5	73.1	
Fuel Consumption:	L/Hr	US Gal/Hr	
Prime:	12.9	3.408	
Standby:	14.3	3.778	

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights

Len	gth	Wi	dth	He	eight		Dry		Wet
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
1941.0	76.4	790.0	31.1	1465.0	57.7	789.0	1739.4	810.0	1785.7

Rating Definition



These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	60Hz		
	M³/min	Ft³/min	
Combustion Air Flow:	3.9	138	
Exhaust Gas Flow:	9.5	335	
Radiator Cooling: Air Flow	70.0	2472	

^{*}Cooling system designed to operate in high ambient conditions

Leroy Somer
LSA42.3M7
Single (1)
Н
at no load <3%
12
IP 23
Shunt
2/3 - 6



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

Logos and Brands of Perkins, Leroy Somer, ABB & Deep Sea Electronics are registered Trademarks

Cooling & Lubrication	60	60Hz		
	Liter	US/Gal		
Coolant Capacity:	10.2	2.7		
Lube Oil Capacity:	8.3	2.2		
	°C	°F		
Exhaust Temperature:	551	1024		



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warranty statement for more details.

Picture shown in leaflet may include optional accessories, all data is correct at the time of process and we reserve the right to change specification without prior notice

Distributed & Serviced by:



2104/2020