



# MP569-MP624E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Output Rating at - 60Hz					
220/127v	KVA	KW			
Prime	569.0	455.2			
Standby	624.0	499.2			
		@ 0.8 p.f.			
Generator Outp	out Rating at	- 60Hz			
380/220V	KVA	KW			
Prime	562	450			
Standby	625	500			
		@ 0.8 p.f.			
Engine Data					
<b>Engine Manufact</b>	urer:	Perkins Seguin			
Engine Model:	25	2506A-E15TAG4			
Number of Cylind	lers:	6			
Cylinder Arrange	ment: Ve	Vertical In Line			
Cycle:		4 Stroke			
Bore/Stroke mm	(in): 137.0	137.0 (5.4) / 171.0 (6.7)			
Induction:		Turbo charged & air - to - air Charge cooled			
Compression rati	o:	16:1			
Displacement / (c	u.in):	15.2 (927.6)			

<b>US/Gal</b> 248.3			
248.3			
Powder Coated Steel			
Heavy Duty-Powder Coated			
Deep Sea Electronics			
ABB 3 Pole MCCB			
,			

601	ΗZ	
1800		
kWm	Bhp	
519.0	696.0	
568.0	762.0	
L/Hr	US Gal/Hr	
115	26.68	
125	30.11	
	kWm 519.0 568.0 L/Hr 115	

#### **Standard Reference Conditions:**

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

\* With Lube Oil & Coolant

Please consult your dealer for specific site ratings.

\* With Lube Oil

## **Dimensions and Weights**

Len	gth	Wic	lth	He	ight	I	Dry	1	Wet
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
3871.0	152.4	1120.0	44.1	2130.0	83.9	3747.0	8260.0	3847.0	8481.0

### **Rating Definition**



# Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow 60Hz			)Hz
		M³/min	Ft³/min
Combustion Air Flow:		42.0	1483
Exhaust Gas Flow:		112.0	3955
Radiator Cooling: Air Flow		822.0	29028.7

<sup>\*</sup>Cooling system designed to operate in high ambient conditions

#### **Alternator Data Alternator Model:** Leroy Somer Alternator Manufacturer: LSA47.2M7 **Insulation Class:** Single (1) **Number of Bearings:** Н Wires: 12 **Total Harmonic Content:** <1.5% IP 23 **Excitation System: Ingress Protection Rating:** Shunt **Winding Pitch Code:** 2/3 - 6



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

 $Logos\ and\ Brands\ of\ Perkins,\ Leroy\ Somer,\ ABB\ \&\ Deep\ Sea\ Electronics\ \ are\ registered\ Trademarks$ 

Cooling & Lubrication	60Hz		
	Liter	US/Gal	
Coolant Capacity:	58.0	15.3	
Lube Oil Capacity:	62.0	16.4	
	°C	°F	
Exhaust Temperature:	590	1094	



## **Other Information**

#### **Generating Set Standards**

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

#### Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warranty statement for more details.

Picture shown in leaflet may include optional accessories, all data is correct at the time of process and we reserve the right to change specification without prior notice

# Distributed & Serviced by:

Г			
L			

19/05/2020