

# Jet<sup>®</sup> Generators

POWERED BY:



Generating Set pictured may include optional accessories

## GENERATING SET MODEL (JP2250)

Output Ratings	Prime	Standby
380-415 V, 3 ph, 50 Hz, 1500 rpm	2250 KVA	2500 KVA
	1800 KW	2000 KW

Ratings at 0.8 Power Factor

## ENGINE / TECHNICAL DATA

Engine Make	Perkins	
Engine Model	4016-61TRG3	
Governing Type	Electronic	
Number of Cylinders	16	
Cylinder Arrangement	60° Vee	
Bore and Stroke mm	160 x 190	
Displacement / Cubic Capacity litres	61.123	
Induction System	Turbocharged	
Cycle	4 stroke, compression ignition	
Combustion System	Direct Injection	
Compression Ratio	13:1 nominal	
Rotation	Anti-clockwise, viewed on flywheel end	
Cooling System	Water	
Frequency and Engine Speed	50Hz & 1500rpm	
	Prime	Standby
Gross Engine Power kWb	1975	2183
Fuel Consumption @ 50% load L/hr	234	-
@ 75% load L/hr	344	-
@ 100% load L/hr	470	529
Total Lubrication System Capacity litres	213	213
Total Coolant Capacity litres (Jacket Water/Secondary Water)	270/230	270/230
Boost Pressure Ratio	4.0	4.0
Exhaust Temperature: °C	475	560
Radiator Cooling Air Flow (Min): m <sup>3</sup> /sec	55.3	55.3
Combustion Air Flow: m <sup>3</sup> /min	160	175
Exhaust Gas Flow: m <sup>3</sup> /min	525	525
Fuel Tank Capacity: litres	N/A	N/A

## DIMENSIONS AND WEIGHT

Length cm	Width cm	Height cm	Weight* kg
586	219	375	15700

\* For skid mounted genset without enclosure

## STANDARD SPECIFICATIONS

### 1. ENGINE

Perkins four stroke heavy duty high performance industrial type diesel engine.

### 2. ENGINE FILTRATION SYSTEM

- Four Cartridge type dry air filters.
- Two Cartridge type fuel filters.
- Six Full flow lube oil filters.

All filters have replaceable elements.

### 3. TROPICAL COOLING RADIATOR

Radiator and cooling fan, complete with safety guards, designed to cool the engine at high ambient temperatures (consult your dealer for de-rating factors)

### 4. EXHAUST SYSTEM

Heavy duty Industrial Exhaust Silencer

Silencer noise reduction level	-
Maximum allowable back pressure	6.6 (kPa)

### 5. CIRCUIT BREAKER TYPE

ABB 3 pole ACB (supplied disconnected and without cables)\*. (4 pole is optional)

(contd.)

## ALTERNATOR DATA

Make	Leroy Somer
Model	LSA51.2VL90
No. of bearings	1
Insulation class	H
Total Harmonic Content	<3.5%
Wires	6
Ingress Protection	IP23
Excitation System	AREP
Winding Pitch	2/3 (n° 6S)
AVR Model	R449
Overspeed	2250 mn <sup>-1</sup>
Voltage Regulation (steady)	± 0.5%
Short Circuit Capacity	300% (3 In):10s

PMG Excitation System Available as Optional.

## CONTROL PANEL

Make	Deep Sea
Model	DSE7320

DSE7320 is an Auto Mains (Utility) Failure Control Module. It is operated via the START, STOP, AUTO and MANUAL soft touch membrane buttons on the front panel. DSE7320 can be controlled remotely using either a GSM Modem, Ethernet via DSE860/865 or via RS485.

### Protection:

- Fail to start
- Low oil pressure
- High engine temperature
- U/O Voltage shutdown
- U/O Frequency shutdown
- Underspeed, Overspeed
- Loss of engine speed detection
- High/Low battery voltage
- kW overload
- Unbalanced load
- Low fuel alarm (if fitted)
- Battery charger failure (if fitted)

(Please refer to DSE7320 brochure for more details)

**AN INSPIRED DESIGN TO MEET YOUR NEEDS**



**RATINGS DEFINITION**

**Prime Power**

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. 10% overload power is available for 1 hour in 12 hours continuous operation.

**Standby Power**

These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings.

**STANDARD REFERENCE CONDITIONS**

Output ratings are presented at 25°C air inlet temperature, barometric pressure 100 kPa, relative humidity 30%. This generating set is designed to operate at high ambient temperatures (up to 55°C), humidity (up to 99%) and higher altitudes. De-rating may apply, please consult your dealer for specific site ratings.

Some of the specifications are not standard on all Genset models.

**AVAILABLE OPTIONS & ACCESSORIES**

We offer a range of optional features and accessories to tailor our generating sets to meet your power needs.

**OPTIONS**

- A variety of generating set control and synchronizing panels
- Additional protection alarms and shutdowns
- Water fuel separator
- Water jacket heater
- Battery charger

**ACCESSORIES**

- Genuine spare parts
- Load banks
- Auxiliary fuel tanks
- Manual & automatic transfer switches



Distributed and Serviced by:

For further information on all of the standard and optional features accompanying this product please contact your local dealer or visit [www.JubailiBros.com](http://www.JubailiBros.com)



JET Generators are assembled in facilities certified to ISO 9001

All information in this document is substantially correct at time of printing and may be altered subsequently.

**STANDARD SPECIFICATIONS**

**6. FUEL SYSTEM**  
On Generating Sets up to 700 KVA, the baseframe design is incorporated with an integral fuel tank with a capacity of approx. 8 hours running at Full Load. The tank is supplied complete with fill cap breather, fuel feed and return lines to the Engine and drain plug.

**7. ALTERNATOR**  
**7.1 INSULATION SYSTEM**

- The insulation system is Class H.
- All windings are impregnated in either a triple dip thermosetting liquid, oil and acid resisting polyester varnish or vacuum pressure impregnated with a special polyester resin.
- Heavy coat of antitracking varnish additional protection against moisture or condensation.

**7.2 AUTOMATIC VOLTAGE REGULATOR (AVR)**  
The fully sealed Automatic Voltage Regulator maintains the Voltage Regulation at  $\pm 0.5\%$ . Nominal adjustment by means of a trim pot incorporated on the AVR.

**7.3 MOTOR STARTING**  
An overload capacity equivalent to 300% of the Full Load impedance at zero Power Factor can be sustained for 10 seconds.

**8. MOUNTING ARRANGEMENT**  
**8.1 BASE FRAME**  
The complete Generating Set is mounted as a whole on a heavy duty fabricated steel Baseframe.

**8.2 COUPLING**  
The Engine and Alternator are directly coupled by means of an SAE flange. The Engine flywheel is flexibly coupled to the Alternator rotor.

**8.3 ANTI-VIBRATION MOUNTING PADS**  
Anti-Vibration pads are affixed between the Engine / Alternator feet and the Baseframe thus ensuring complete vibration isolation of the rotating assembly.

**8.4 SAFETY GUARDS**  
The Fan & Fan Drive along with the Battery Charging Alternator are Safety Guard protected for personnel protection.

**9. FACTORY TESTS**

- The Generating set is load tested before dispatch
- All protective devices control functions and site load conditions are simulated. The generator and it's systems are checked before dispatch.

**10. EQUIPMENT FINISHING**  
All mild steel components are fully degreased and painted with powder coated paint to ensure maximum scuff resistance and durability.

**11. DOCUMENTATIONS**  
Operation & Maintenance manual, Circuit wiring diagrams and Commissioning / Fault Finding instruction leaflets are accompanied with the Generator.

**12. QUALITY STANDARDS**  
The equipment meets the following standards: BS4999, BS5000, BS5514 IEC 60034, VDE0530, NEMA MG 1.22 and ISO 8528.

**13. WARRANTY**  
All of the Generating Sets are covered under a warranty policy for a period of 12 months. Warranty of the equipment is in line with manufacturers warranty terms & conditions.  
(check warranty statement for more details, as it may vary for different countries)

In line with continuous product development, we reserve the right to change specifications without notice.