



MP1100E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Outp	out Rating a	t - 50Hz	
400V	KVA		KW
Prime	1000.0		800.0
Standby	1100.0		880.0
			@ 0.8 p.f.
Generator Outp	out Rating a	t - 60Hz	
480V	KVA		KW
Prime	N/A		N/A
Standby	N/A		N/A
			@ 0.8 p.f.
Engine Data			
Engine Manufacturer: Perkins UK			
Engine Manufact	urer:	Perkins l	JK
Engine Manufacti Engine Model:		Perkins (4008-30T/	
Engine Model:	lers:	4008-30T/	AG2
Engine Model: Number of Cylind	lers:	4008-30T/ 8	AG2 Line
Engine Model: Number of Cylind Cylinder Arranger	lers: ment:	4008-30T/ 8 Vertical In	AG2 Line e
Engine Model: Number of Cylind Cylinder Arranger Cycle:	lers: ment: ' (in): 160.0 Turbo	4008-30T/ 8 /ertical In 4 Strok 0 (6.3) / 19	AG2 Line e 00.0 (7.5) a air-to-air
Engine Model: Number of Cylind Cylinder Arranger Cycle: Bore/Stroke mm	lers: ment: (in): 160.0 Turbo	4008-30T/ 8 /ertical In 4 Strok 0 (6.3) / 19 charged 8	AG2 Line e 00.0 (7.5) a air-to-air

General Data					
	Liter	US/Gal			
Fuel Tank Capacity:	N/A	N/A			
Fuel Tank:	N/A				
Base Frame:	Heavy Duty-Powder Coated				
Control Panel:	Deep Sea Electronics				
Circuit Breaker:	ABB 3 Pole MCB				

Performance	50	50Hz		60HZ	
Engine Speed:	15	1500		1800	
Gross Engine Power:	kWm	kWm Bhp		Bhp	
Prime:	901	1205.6	N/A	N/A	
Standby:	997	1320.9	N/A	N/A	
Fuel Consumption:	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr	
Prime:	223	58.12	N/A	N/A	
Standby:	234	65.51	N/A	N/A	

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights

Len	gth	Wi	dth	He	ight		Dry		Wet
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
4649.0	183.0	2125.0	83.7	2363.0	93.0	7030.0	15498.0	7328.0	16155.0

* With Lube Oil & Coolant

Rating Definition



These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50Hz		60Hz	
	M³/min	Ft³/min	M³/min	Ft³/min
Combustion Air Flow:	84	2843	N/A	N/A
Exhaust Gas Flow:	203	7063	N/A	N/A
Radiator Cooling: Air Flow	1140	47675	N/A	N/A

^{*}Cooling system designed to operate in high ambient conditions

Alternator Data

Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA49.3 L10 TAL049E
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Content:	< 4% < 5%
Wires:	6
Ingress Protection Rating:	IP 23
Excitation System:	AREP Shunt



Winding Pitch Code:

Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.

2/3 - 6S



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

 $Logos\ and\ Brands\ of\ Perkins,\ Leroy\ Somer,\ ABB\ \&\ Deep\ Sea\ Electronics\ \ are\ registered\ Trademarks$

Cooling & Lubrication	50Hz		60Hz	
	Liter	US/Gal	Liter	US/Gal
Coolant Capacity:	140.0	39.4	N/A	N/A
Lube Oil Capacity:	153.0	40.4	N/A	N/A
	°C	°F	°C	°F
Exhaust Temperature:	473	869	N/A	N/A

Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:



JAN2014 VER.1