



MP150E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Output R	ating at -	50H	z		
400V	KVA		KW		
Prime 1	135.0		108.0		
Standby 1	150.0		120.0		
			@ 0.8 p.f.		
Generator Output R	ating at -	60H	Z		
480V	KVA		KW		
Prime 1	152.0		122.0		
Standby	169.0		135.0		
			@ 0.8 p.f.		
Engine Data					
Engine Manufacturer:	F	Perkins UK			
Engine Model:	1106A-70TG1				
Number of Cylinders: 6					
Cylinder Arrangement:	vlinder Arrangement: Vertical In Line		In Line		
		tiou.	III LIIIC		
Cycle:		4 Str			
Cycle: Bore/Stroke mm (in):		4 Str			
•	105.0 (4 Turbo ch	4 Str 4.1) x argeo	oke		
Bore/Stroke mm (in):	105.0 (4 Turbo ch	4 Str 4.1) x argeo	oke 135.0 (5.3) d & air-to-air cooled		

General Data			
	Liter	US/Gal	
Fuel Tank Capacity:	400.0	105.7	
Fuel Tank:	Powder Coated Steel		
Base Frame:	Heavy Duty-Powder Coated		
Control Panel:	Deep Sea Electronics		
Circuit Breaker:	ABB 3 Pole MCB		

800
Bhp
188.0
208.0
US Gal/Hr
9.298
10.24

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights

Len	gth	Wic	lth	Hei	ght		Dry		Wet
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
2683.0	105.6	1000.0	39.4	1670.0	65.7	1725.0	3803.0	1748.0	3845.0

* With Lube Oil & Coolant

Rating Definition



These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50Hz	60Hz		
	M³/min Ft³/mir	n M³/min Ft³/min		
Combustion Air Flow:	8.09 286	11.86 419		
Exhaust Gas Flow:	22.66 800	29.72 1049.5		
Radiator Cooling: Air Flow	182 6427	182 6427		

^{*}Cooling system designed to operate in high ambient conditions

Alternator Data

Alternator Bata	
Alternator Manufacturer:	Leroy Somer
Alternator Model: LS	SA44.3 M8 TALO44H
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Distortion:	< 5%
Wires:	12 6
Ingress Protection Rating:	IP 23
Excitation System:	Shunt
Winding Pitch Code:	2/3 - 6



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

 $Logos\ and\ Brands\ of\ Perkins,\ Leroy\ Somer,\ ABB\ \&\ Deep\ Sea\ Electronics\ \ are\ registered\ Trademarks$

Cooling & Lubrication	50Hz		60Hz	
	Liter	US/Gal	Liter	US/Gal
Coolant Capacity:	21.0	5.5	21.0	5.5
Lube Oil Capacity:	18.0	4.7	18.0	4.7
	°C	°F	°C	°F
Exhaust Temperature:	576	1069	526	979



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:



7-2015 REV.1