



MP1650E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Out	out Rating at	- 50Hz			
400V	KVA	KW			
Prime	1500.0	1200.0			
Standby	1650.0	1320.0			
		@ 0.8 p.f.			
Generator Outp	out Rating at	- 60Hz			
480V	KVA	KW			
Prime	N/A	N/A			
Standby	N/A	N/A			
		@ 0.8 p.f.			
Engine Data					
Engine Manufacturer: Perkins UK					
Engine Model:	40	012-46TAG2A			
Number of Cylind	lers:	12			
Cylinder Arrange	ment:	60 Vee			
Cycle:		4 Stroke			
Bore/Stroke mm	re/Stroke mm (in): 160.0 (6.3) / 190.0 (7.5)				
Induction:		Turbo charged & air to air charge cooled			
Compression rati	0:	13:1			
Displacement <i>I</i> (<i>cu.in</i>): 45.8 (2797.5)					

General Data				
	Liter	US/Gal		
Fuel Tank Capacity:	N/A	N/A		
Fuel Tank:	N/A			
Base Frame:	Heavy Duty-Powder Coated			
Control Panel:	Deep Sea Electronics			
Circuit Breaker:	ABB 3 Pole MCB			

Performance	50	50Hz		HZ
Engine Speed:	150	1500		00
Gross Engine Power:	kWm	kWm Bhp		Bhp
Prime:	1331.0	1784.9	N/A	N/A
Standby:	1459.0	1956.6	N/A	N/A
Fuel Consumption:	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr
Prime:	309.0	81.6	N/A	N/A
Standby:	340.0	89.8	N/A	N/A

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights

						<u> </u>			
Len	gth	Wi	dth	Hei	ght		Dry		Wet
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
4835.0	190.4	2624.0	103.3	2453.0	96.6	8762.0	19317.0	8962.0	19758.0
						* With Lube Oi		* With Lube Oil	& Coolant

Rating Definition

P Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

Standby Rating

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50H	z 60	Hz
	M∛min Ft	∛min M³/min	Ft∛min
Combustion Air Flow:	128.0 4	520 N/A	N/A
Exhaust Gas Flow:	320.0 11	1301 N/A	N/A
Radiator Cooling: Air Flow	1872.0 66	5109 N/A	N/A

*Cooling system designed to operate in high ambient conditions

Alternator Data	
Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA50.2 L8
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Content:	< 3.5%
Wires:	6
Ingress Protection Rating:	IP 23
Excitation System:	AREP
Winding Pitch Code:	2/3 - 6S



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

Logos and Brands of Perkins, Leroy Somer, ABB & Deep Sea Electronics are registered Trademarks

Cooling & Lubrication	50Hz		60Hz		
	Liter	US/Gal	Liter	US/Gal	
Coolant Capacity:	210.0	58.1	N/A	N/A	
Lube Oil Capacity:	177.0	46.9	N/A	N/A	
	°C	°F	°C	°F	
Exhaust Temperature:	455	851	N/A	N/A	



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:



Marapco Ltd 8 Meadowbank Rd - Carrickfergus - N. Ireland - U.K. BT38 8YF Tel: +44 (0) 2893 355674 - www.marapco.com - Email: sales@marapco.com