



# **MP200E**

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Output F	Rating at -	50Hz		
400V	KVA		KW	
Prime	180.0		160.0	
Standby	200.0		176.0	
			@ 0.8 p.f.	
Generator Output F	Rating at -	60Hz		
480V	KVA		KW	
Prime	168.8		135.0	
Standby	187.5		150.0	
			@ 0.8 p.f.	
Engine Data				
Engine Manufacturer: Perkins UK				
Engine Manufacturer:	Pe	rkins UK		
Engine Manufacturer: Engine Model:		rkins UK 5A-70TA		
Engine Model:	1106	6A-70TA	G3	
Engine Model: Number of Cylinders:	1106 :: Vert	6 6	G3	
Engine Model: Number of Cylinders: Cylinder Arrangement	1106 :: Vert	6 6 ical In Li	G3 ne	
Engine Model: Number of Cylinders: Cylinder Arrangement Cycle:	1106 :: Vert 4 105.0 (4. Turbo cha	6 6 ical In Li Stroke 1) / 135		
Engine Model: Number of Cylinders: Cylinder Arrangement Cycle: Bore/Stroke mm (in):	1106 :: Vert 4 105.0 (4. Turbo cha	6 6 ical In Li Stroke 1) / 135 rged & a		

General Data			
	Liter	US/Gal	
Fuel Tank Capacity:	400.0	116.2	
Fuel Tank:	Powder Coated Steel		
Base Frame:	Heavy Duty-Powder Coated		
Control Panel:	Deep Sea Electronics		
Circuit Breaker:	ABB 3 Pole MCB		

1800	
kWm	Bhp
155.4	208.4
171.8	230.4
L/Hr	US Gal/Hr
38.2	10.1
41.7	11.0
	kWm 155.4 171.8 L/Hr 38.2

#### **Standard Reference Conditions:**

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

\* With Lube Oil & Coolant

Please consult your dealer for specific site ratings.

\* With Lube Oil

## **Dimensions and Weights**

Len	gth	Wic	lth	He	ight	[	Dry	1	Wet
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
2903.0	114.3	1000.0	39.4	1770.0	69.7	1820.0	4012.4	1878.0	4140.0

#### **Rating Definition**



# **Prime Rating**

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



# **Standby Rating**

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50Hz	60Hz	
	M³/min Ft³/min	M³/min Ft³/min	
Combustion Air Flow:	13.2 466.1	16.37 N/A	
Exhaust Gas Flow:	36.8 1299.5	38.35 N/A	
Radiator Cooling: Air Flow	222.0 7840	282 N/A	

<sup>\*</sup>Cooling system designed to operate in high ambient conditions

### **Alternator Data**

Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA 46.3 S2   TALO46A
Number of Bearings:	Single (1)
Insulation Class:	Н
<b>Total Harmonic Distortion:</b>	< 2.5%   < 5%
Wires:	12   6
Ingress Protection Rating:	IP 23
Excitation System:	Shunt
Winding Pitch Code:	2/3 - 6



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

 $Logos\ and\ Brands\ of\ Perkins,\ Leroy\ Somer,\ ABB\ \&\ Deep\ Sea\ Electronics\ \ are\ registered\ Trademarks$ 

Cooling & Lubrication	50Hz		60Hz	
	Liter	US/Gal	Liter	US/Gal
Coolant Capacity:	21.0	5.55	20.5	5.42
Lube Oil Capacity:	18.0	4.75	18.0	4.75
	°C	°F	°C	°F
Exhaust Temperature:	491	915	407	765



#### **Other Information**

#### **Generating Set Standards**

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

#### Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

## Distributed & Serviced by:



7-2015 REV.1