

MP220E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Out	out Ratir	ng at -	50H	Z
400V	KVA			KW
Prime	200.0			160.0
Standby	220.0			176.0
				@ 0.8 p.f.
Generator Out	out Ratir	ng at -	60H	Z
480V	KVA	4		KW
Prime	225	.0		180.0
Standby	250.0			200.0
				@ 0.8 p.f.
Engine Data				
Engine Manufact	urer:	P	erkir	is UK
Engine Manufact Engine Model:	urer:			os UK 'OTTAG1
				OTTAG1
Engine Model:	ders:	1206	6A-E7	OTTAG1
Engine Model: Number of Cylind	ders:	1206	6A-E7	OTTAG1
Engine Model: Number of Cylind Cylinder Arrange	ders: ment:	1206 Vei	6A-E7 6 rtical 4 Str	OTTAG1
Engine Model: Number of Cylind Cylinder Arrange Cycle:	ders: ment: (in):	1200 Ver 105(4 Twin tu	6A-E7 6 rtical 4 Str I.1) x	OTTAG1 In Line oke
Engine Model: Number of Cylind Cylinder Arrange Cycle: Bore/Stroke mm	ders: ment: (in):	1200 Ver 105(4 Twin tu	6A-E7 6 rtical 4 Str I.1) x	In Line oke 135 (5.3) & air-to-air cooled

Liter	US/Gal			
600.0	158.5			
Powder Coated Steel				
Heavy Duty-Powder Coated				
Deep Sea Electronics				
ABB 3 Pole MCCB				
	600.0 Powder Co Heavy Duty-Po Deep Sea B			

Performance	50H	50Hz		HZ
Engine Speed:	150	1500		00
Gross Engine Power:	kWm	Bhp	kWm	Bhp
Prime:	185.8	249.2	216.6	290.5
Standby:	204.2	273.8	238.6	320.0
Fuel Consumption:	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr
Prime:	45.8	12.1	54.5	14.4
Standby:	51.0	13.5	61.1	16.1

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights

Len	gth	Wic	lth	Hei	ght	[Dry		Wet
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
3500.0	137.8	1096.0	43.1	1820.0	71.6	2315.0	5103.7	2345.0	5169.8
					* With Lube Oil		* With Lube Oi	l & Coolant	

Rating Definition



These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50Hz		60Hz	
	M³/min	Ft³/min	M³/min	Ft³/min
Combustion Air Flow:	13.5	477	18.6	657
Exhaust Gas Flow:	31.9	1126	42.1	1487
Radiator Cooling: Air Flow	370	13066	482	17022

^{*}Cooling system designed to operate in high ambient conditions

Alternator Data

Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA46.3 S3 TAL046B
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Distortion:	< 2.5% < 5%
Wires:	12 6
Ingress Protection Rating:	IP 23
Excitation System:	Shunt
Winding Pitch Code:	2/3 (n° 6)



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

 $Logos\ and\ Brands\ of\ Perkins,\ Leroy\ Somer,\ ABB\ \&\ Deep\ Sea\ Electronics\ \ are\ registered\ Trademarks$

Cooling & Lubrication	50	50Hz		OHz
	Liter	US/Gal	Liter	US/Gal
Coolant Capacity:	25	6.6	25	6.6
Lube Oil Capacity:	16	4.2	16	4.2
	°C	°F	°C	°F
Exhaust Temperature:	487	909	500	932

Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:



2103/2016