



MP2000E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Output Rating at - 50Hz						
400V	KVA		KW			
Prime	1850.0		1480.0			
Standby	2000.0		1600.0			
			@ 0.8 p.f.			
Generator Outp	out Rating at	- 60Hz				
480V	KVA		KW			
Prime	N/A		N/A			
Standby	N/A		N/A			
			@ 0.8 p.f.			
Engine Data						
Engine Manufa	acturer:	Perk	ins UK			
Engine Model:		4016-	61TRG1			
Number of Cyl	inders:		16			
Cylinder Arrangement:		60°Vee				
Cycle:		4 S	troke			
Bore/Stroke mm (in):		160.0 (6.3) / 190.0 (7.5)				
Induction:		Turbocharged				
Compression r	atio:	1	3:1			
Displacement	l (cu.in):	61.123	3 (3729)			

General Data						
	Lit	ter		US/G	Gal	
Fuel Tank Capacity:	N	/A		N/	A	
Fuel Tank:	Tank: N/A					
Base Frame:	me: Heavy Duty-Powder Coated					
Control Panel:	rol Panel: Deep Sea Electronics					
Circuit Breaker:	Circuit Breaker: ABB 3 Pole ACB					
*Breaker supplied loose	in a standalor	e cabinet on	open ty	pe gene	rating sets	
Performance 50Hz 60Hz						
					l .	
Engine Speed:		1500		18	00	
Engine Speed: Gross Engine Power				180 kWm	00 <i>Bhp</i>	
		n Bhp				
Gross Engine Power	: kWi	m Bhp 8 2210		kWm	Вһр	
Gross Engine Power Prime: Standby:	164 177	m Bhp 8 2210 4 2379		kWm N/A N/A	Bhp N/A N/A	
Gross Engine Power Prime:	kWi	m Bhp 8 2210 4 2379 r Us Gal/H		kWm N/A	Bhp N/A	
Gross Engine Power Prime: Standby: Fuel Consumption:	: kWi 164 177	m Bhp 8 2210 4 2379 r Us Gal/H 98		kWm N/A N/A	Bhp N/A N/A US Gal/Hr	

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights									
Len	gth	Wid	th	Hei	ght	D	ry	W	et
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
5623	221.3	2225	87.6	3549	139.7			13500	29762
		* With Lube Oi		* With Lube Oil	& Coolant				

Rating Definition



Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



Standby Rating

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50	Hz	60	60 Hz		
	M³/min	Ft³/min	M³/min	Ft³/min		
Combustion Air Flow:	165	5827	N/A	N/A		
Exhaust Gas Flow:	400	14126	N/A	N/A		
Radiator Cooling Air Flow:	2160	78399	N/A	N/A		

^{*}Cooling system designed to operate in high ambient conditions

Alternator Data

Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA52.3 S5
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Content:	< 4%
Wires:	6
Ingress Protection Rating:	IP 23
Excitation System:	AREP + PMI
Winding Pitch Code:	2/3 - (n°6S)

Principles



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

Logos and Brands of Perkins, Leroy Somer, ABB & Deep Sea Electronics are Registered Trademarks

Cooling & Lubrication	5(0 Hz	60 Hz	
Coolant Capacity: Lube Oil Capacity:	Liter 385 213	<i>US/Gal</i> 55.5 56.3	Liter N/A N/A	US/Gal N/A N/A
Exhaust Temperature:	°C 425	°F 752	°C N/A	°F N/A



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warranty statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:



2106/2017