



# **MP2200E**

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Outp	out Rating a	t - 50Hz			
400V	KVA		KW		
Prime	2000.0		1600.0		
Standby	2200.0		1760.0		
			@ 0.8 p.f.		
Generator Outp	out Rating a	t - 60Hz			
480V	KVA		KW		
Prime	N/A		N/A		
Standby	N/A		N/A		
			@ 0.8 p.f.		
Engine Data					
<b>Engine Manufact</b>	urer:	Perkins UK			
Engine Model:		4016TAG2A			
Number of Cylind	ders:	16			
Cylinder Arrange	ment:	60° Vee			
Cycle:		4 Stroke			
Bore/Stroke mm	(in): 160	160 x 190 (6.3) x (7.5)			
Induction:	Induction: Turboo		narged & air to air		
		charge cooled			
Compression rati	0:	13.6:1			
Displacement / (c	ru.in):	61.123 (3729)			

General Data							
		Lit	er	US/G	al		
Fuel Tank Capacity:		N,	/A	N/A			
Fuel Tank:			N/A				
Base Frame:	H	leavy [	Outy-Pov	vder Co	ated		
<b>Control Panel:</b>	control Panel: Deep Sea Electronics						
Circuit Breaker:	ABB 3 Pole ACB						
*Breaker supplied loose in a standalone cabinet on open type generating sets							
Performance		50Hz		60HZ			
Engine Speed:		1500		1800			
<b>Gross Engine Power:</b>		kWb	Bhp	kWm	Bhp		
Prime:		1766	2368.2	N/A	N/A		
Standby:		1937	2597.5	N/A	N/A		
Fuel Consumption:		L/Hr	US Gal/Hr	L/Hr	US Gal/Hr		
Prime:		434	114.6	N/A	N/A		
Standby:		483	127.6	N/A	N/A		

#### **Standard Reference Conditions:**

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

# **Dimensions and Weights**

Len	gth	Wi	dth	He	eight	I	Dry		Wet
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
5750.0	227.0	2775.0	109.3	3536.0	139.2	15600.0	34392.0	15780.0	34789.0

\* With Lube Oil & Coolant

## **Rating Definition**



These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50Hz	60Hz
	M³/min Ft³/mi	n M³/min Ft³/min
Combustion Air Flow:	145 5121	N/A N/A
Exhaust Gas Flow:	387 13667	7 N/A N/A
Radiator Cooling: Air Flow	2430 85815	N/A N/A

<sup>\*</sup>Cooling system designed to operate in high ambient conditions

#### Alternator Data **Alternator Manufacturer: Leroy Somer Alternator Model:** LSA52.3 S6 **Number of Bearings:** Single (1) **Insulation Class:** Н **Total Harmonic Distortion:** < 4% Wires: IP 23 **Ingress Protection Rating:** AREP + PMI **Excitation System: Winding Pitch Code:** 2/3 - 6



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

 $Logos\ and\ Brands\ of\ Perkins,\ Leroy\ Somer,\ ABB\ \&\ Deep\ Sea\ Electronics\ \ are\ registered\ Trademarks$ 

Cooling & Lubrication	50Hz		60Hz		
	Liter	US/Gal	Liter	US/Gal	
Coolant Capacity:	316	83.5	N/A	N/A	
Lube Oil Capacity:	214	56.5	N/A	N/A	
	°C	°F	°C	°F	
Exhaust Temperature:	493	919	N/A	N/A	



### **Other Information**

#### **Generating Set Standards**

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

#### Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

## Distributed & Serviced by:



2708/2017