



MP2250E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Output	Pating a	F _ 50Hz					
-	i Natiliy a	l - 50HZ					
400V	KVA		KW				
Prime	2000.0		1600.0				
Standby	2250.0		1800.0				
			@ 0.8 p.f.				
Generator Output Rating at - 60Hz							
480V	KVA		KW				
Prime	N/A		N/A				
Standby	N/A		N/A				
			@ 0.8 p.f.				
Engine Data							
Engine Manufacture	er:	Perkins	UK				
Engine Manufacture Engine Model:		Perkins 4016-611					
Engine Model:	s:	4016-617	ΓRG2				
Engine Model: Number of Cylinder	s:	4016-617 16	rRG2				
Engine Model: Number of Cylinder Cylinder Arrangeme	s: ent:	4016-611 16 60° Ve 4 Strol	rRG2				
Engine Model: Number of Cylinder Cylinder Arrangeme Cycle:	s: ent:): 160	4016-611 16 60° Ve 4 Strol	rRG2 ee ke 3) x (7.5)				
Engine Model: Number of Cylinder Cylinder Arrangeme Cycle: Bore/Stroke mm (in	s: ent:): 160	4016-617 16 60° Ve 4 Strol x 190 (6.	rRG2 ee ke 3) x (7.5) rged				

General Data						
	Lit	er	US/G	al		
Fuel Tank Capacity:	N,	/A	N/A			
Fuel Tank:	N/A					
Base Frame:	Heavy Duty-Powder Coated					
Control Panel:	Panel: Deep Sea Electronics					
Circuit Breaker:	ABB 3 Pole ACB					
*Breaker supplied loose in a standalone cabinet on open type generating sets						
Performance	50Hz 60HZ			HZ		
Engine Speed:	15	1500		00		
Gross Engine Power:	kWb	Bhp	kWm	Bhp		
Prime:	1774	2378.9	N/A	N/A		
Standby:	1985	2662	N/A	N/A		
Standby: Fuel Consumption:	1985 L/Hr	2662 US Gal/Hr	N/A L/Hr	N/A US Gal/Hr		
-				,		
Fuel Consumption:	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr		

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights									
Leng	gth	Wic	Width Height		Height		Ory	Wet	
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
						* With Lube Oil		* With Lube Oil	& Coolant

Rating Definition



These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50	Hz	601	Hz
	M³/min	Ft³/min	M³/min	Ft³/min
Combustion Air Flow:	175	6180	N/A	N/A
Exhaust Gas Flow:	475	16775	N/A	N/A
Radiator Cooling: Air Flow	2820	99587	N/A	N/A

^{*}Cooling system designed to operate in high ambient conditions

Alternator Data **Alternator Manufacturer: Leroy Somer** LSA52.3 L9 **Alternator Model: Number of Bearings:** Single (1) **Insulation Class:** Н **Total Harmonic Content:** < 4% Wires: IP 23 **Ingress Protection Rating:** AREP + PMI **Excitation System: Winding Pitch Code:** 2/3 - 6



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

 $Logos\ and\ Brands\ of\ Perkins,\ Leroy\ Somer,\ ABB\ \&\ Deep\ Sea\ Electronics\ \ are\ registered\ Trademarks$

Cooling & Lubrication	50Hz		60Hz	
	Liter	US/Gal	Liter	US/Gal
Coolant Capacity:	552	145.8	N/A	N/A
Lube Oil Capacity:	213.0	56.5	N/A	N/A
	°C	°F	°C	°F
Exhaust Temperature:	488	910	N/A	N/A



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:



2708/2017