



MP2500E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Ou	Itput Ratin	g at - 50Hz				
400V	KVA		КW			
Prime	2250		1800.0			
Standby	2500		2000.0			
			@ 0.8 p.f.			
Generator Output Rating at - 60Hz						
480V	KVA		KW			
Prime	N/A		N/A			
Standby	N/A		N/A			
			@ 0.8 p.f.			
Engine Data						
Engine Manufacturer:		Perkins UK				
Engine Model:		4016-61TRG3				
Number of Cylinders:						
Number of Cy	linders:	16				
Number of Cy Cylinder Arrar		16 60° V				
			/ee			
Cylinder Arrar	ngement:	60° V	′ee ke,			
Cylinder Arran Cycle:	ngement:	60° V 4 Stro	′ee ke, .3) x (7.5)			
Cylinder Arran Cycle: Bore/Stroke n	ngement: nm (in):	60° V 4 Stro 160 x 190 (6	′ee ke, .3) x (7.5) arged			

e East, Asia & Amca.							
General Data							
	Lite	r	US/	US/Gal			
Fuel Tank Capacity:	N/A	λ	N/A				
Fuel Tank: N/A							
Base Frame:	Base Frame: Heavy Duty-Powder Coated						
Control Panel:	Control Panel: Deep Sea Electronics						
Circuit Breaker:	Circuit Breaker: ABB 3 Pole ACB						
*Breaker supplied loose in			,, ,	-			
Performance 50Hz 60Hz							
Engine Speed:	15	1500		00			
Gross Engine Power:	kWm	Bhp	kWm	Bhp			
Prime:	1975.0	2648.5	N/A	N/A			
Standby:	2183.0	2927.4	N/A	N/A			
Fuel Consumption:	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr			
Prime:	470	124.1	N/A	N/A			
Standby:	529	139.7	N/A	N/A			

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

Dimensions and Weights									
Len	gth	Wid	th	Hei	ght		Dry	V	Vet
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
5803	228.4	2225	87.5	3930	154.7			15700	34612.5
* With Lube Oil * With Lube Oil & Coola				il & Coolant					

Marapco Ltd 8 Meadowbank Rd - Carrickfergus - N. Ireland - U.K. BT38 8YF Tel: +44 (0) 2893 355674 - www.marapco.com - Email: sales@marapco.com

Rating Definition

Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

S Standby Rating

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50 Hz		60	Hz
	M∛min	Ft∛min	M∛min	Ft ^³ /min
Combustion Air Flow:	175.0	6180	N/A	N/A
Exhaust Gas Flow:	525.0	18540	N/A	N/A
Radiator Cooling Air Flow:	3320.0	117245	N/A	N/A

*Cooling system designed to operate in high ambient conditions

Alternator Data

Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA52.3 L9
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Distortion:	< 4%
Wires:	6
Ingress Protection Rating:	IP 23
Excitation System:	AREP + PMI
Winding Pitch Code:	2/3 - n° 6S

Principles



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

Logos and Brands of Perkins, Leroy Somer, ABB & Deep Sea Electronics are Registered Trademarks

Cooling & Lubrication	1	50 Hz		60 Hz		
	Liter	US/Gal	Liter	US/Gal		
Coolant Capacity:	500.0	132.1	N/A	N/A		
Lube Oil Capacity:	213.0	56.2	N/A	N/A		
	°C	°F	°C	°F		
Exhaust Temperature:	560	1040	N/A	N/A		



Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warranty statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:



0407/2017

Marapco Ltd 8 Meadowbank Rd - Carrickfergus - N. Ireland - U.K. BT38 8YF Tel: +44 (0) 2893 355674 - www.marapco.com - Email: sales@marapco.com