

MP275E

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Out	out Rating at ·	- 50Hz		
400V	KVA	KW		
Prime	250.0	200.0		
Standby	275.0	220.0		
		@ 0.8 p.f.		
Generator Out	out Rating at ·	- 60Hz		
480V	KVA	KW		
Prime	225.0	180.0		
Standby	250.0	200		
		@ 0.8 p.f.		
Engine Data				
Engine Manufacturer: Perkins UK				
Engine Model:	odel: 1206A-E70TTAG3			
Number of Cylinders: 6				
Cylinder Arrangement: Vertical In		rtical In Line		
Cycle:		4 Stroke		
Bore/Stroke mm	(in): 105 (4.1) x 135 (5.3)			
Induction:	Twin turbo & air-to-air charge cooled			
	••	15.8:1		
Compression rati	0:	13.0.1		

General Data

	Liter	US/Gal	
Fuel Tank Capacity:	600	158.5	
Fuel Tank:	Powder Coated Steel		
Base Frame:	Heavy Duty-Powder Coated		
Control Panel:	Deep Sea Electronics		
Circuit Breaker:	ABB 3 Pole MCCB		

Performance	50Hz		60HZ	
Engine Speed:	150	1500		00
Gross Engine Power:	kWm	Bhp	kWm	Bhp
Prime:	226.2	303.3	217.0	291
Standby:	248.6	333.4	239.6	321.3
Fuel Consumption:	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr
Prime:	56.9	15.0	54.5	14.4
Standby:	64.5	17.0	61.1	16.1

Standard Reference Conditions:

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

* With Lube Oil

Dimensions and Weights Width Wet Length Height Dry Millimeter Millimeter Millimeter KG LB KG LB Inch Inch Inch 3500.0 137.8 1096.0 43.1 1820.0 71.6 2435.0 5368.2 2465.0 5434.4

* With Lube Oil & Coolant

Marapco Ltd 8 Meadowbank Rd - Carrickfergus - N. Ireland - U.K. BT38 8YF Tel: +44 (0) 2893 355674 - www.marapco.com - Email: sales@marapco.com

Rating Definition

P Prime Rating

These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.

S Standby Rating

These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50Hz		60Hz	
	M³∕min	Ft∛min	M∛min	Ft∛min
Combustion Air Flow:	15.7	554	14.0	494
Exhaust Gas Flow: (Prime)	33.66	1189	31.18	1101
Radiator Cooling: Air Flow	265.2	13066	337.2	17022

*Cooling system designed to operate in high ambient conditions

Alternator Data	
Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA46.3 S5 TAL046D
Number of Bearings:	Single (1)
Insulation Class:	Н
Total Harmonic Distortion:	< 2.5% <i><</i> 5%
Wires:	12 6
Ingress Protection Rating:	IP23
Excitation System:	Shunt
Winding Pitch Code:	2/3 (n° 6)



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

Logos and Brands of Perkins, Leroy Somer, ABB & Deep Sea Electronics are registered Trademarks

Cooling & Lubrication	50Hz		60Hz	
	Liter	US/Gal	Liter	US/Gal
Coolant Capacity:	25	6.6	25	6.6
Lube Oil Capacity:	16	4.2	16	4.2
	°C	°F	°C	°F
Exhaust Temperature:	511	952	505	941

Other Information

Generating Set Standards

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

Distributed & Serviced by:



Marapco Ltd 8 Meadowbank Rd - Carrickfergus - N. Ireland - U.K. BT38 8YF Tel: +44 (0) 2893 355674 - www.marapco.com - Email: sales@marapco.com