



# **MP450E**

Since 1994 Marapco Generating Sets have provided reliable, dependable and trustworthy power solutions for the global market. Marapco Generating Sets combine quality and performance to deliver a superior product, making Marapco a market leading Generating Set throughout the Middle East, Asia & Africa.

Generator Output R	ating at -	50H	z	
400V	KVA		KW	
Prime 4	0.004		320.0	
Standby 4	150.0		360.0	
			@ 0.8 p.f.	
Generator Output R	ating at -	60H	Z	
480V	KVA		KW	
Prime 2	140.0		352.0	
Standby	495.0		396.0	
			@ 0.8 p.f.	
Engine Data				
Engine Manufacturer: Perkins USA				
Engine Model:	2206A-E13TAG3			
Number of Cylinders:		6		
Cylinder Arrangement:	ent: Vertical In Line			
Cycle:	4 Stroke			
Bore/Stroke mm (in):	(in): 130.0 (5.1) / 157.0 (6.1)			
Induction:	Turbo charged & air-to-air Charge cooled			
	Ch	arge (	cooled	
Compression ratio:	Ch	arge ( 16.3		

General Data			
	Liter	US/Gal	
Fuel Tank Capacity:	820.0	216.6	
Fuel Tank:	Powder Coated Steel		
Base Frame:	Heavy Duty-Powder Coated		
Control Panel:	Deep Sea Electronics		
Circuit Breaker:	ABB 3 Pole MCB		

Performance	5	50Hz		HZ
Engine Speed:	1	1500 1800		
<b>Gross Engine Power:</b>	kWm	kWm Bhp		Bhp
Prime:	368.4	494.0	373.4	500.7
Standby:	412.5	553.2	406.5	545.1
<b>Fuel Consumption:</b>	L/Hr	US Gal/Hr	L/Hr	US Gal/Hr
Prime:	81	21.4	81	21.4
Standby:	90	23.78	87	22.98

#### **Standard Reference Conditions:**

Output ratings are presented at normal conditions of temperature and pressure. This generator set is designed to operate in high ambient temperatures and altitudes.

Please consult your dealer for specific site ratings.

## **Dimensions and Weights**

Len	gth	Wi	dth	He	eight	I	Dry	,	Wet
Millimeter	Inch	Millimeter	Inch	Millimeter	Inch	KG	LB	KG	LB
3575.0	140.7	1120.0	44.1	2173.0	84.1	3360.0	7407.5	3460.0	7628.0

\* With Lube Oil & Coolant

### **Rating Definition**



These rating are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. This model can supply 10% overload power for 1 hour in 12 hours.



These rating are applicable for supply continuous electrical power (at variable load) in the event of utility power failure. No *overload is permitted on these ratings. The* alternator model is peak continuous rated (as *defined in ISO 8528-3*)

Air Flow	50Hz	60Hz
	M³/min F³/min	M³/min Ft³/min
Combustion Air Flow:	26.4 932	29.0 1024
Exhaust Gas Flow:	72.5 2560	73.5 2596
Radiator Cooling: Air Flow	654.0 23096	788.0 27828

<sup>\*</sup>Cooling system designed to operate in high ambient conditions

## **Alternator Data**

Alternator Manufacturer:	Leroy Somer
Alternator Model:	LSA47.2 S4   TALO47A
Number of Bearings:	Single (1)
Insulation Class:	Н
<b>Total Harmonic Content:</b>	<b>&lt; 2</b> %   <i>&lt;</i> 5%
Wires:	12   6
Ingress Protection Rating:	IP 23
Excitation System:	Shunt
Winding Pitch Code:	2/3 - 6



Perkins manufactures diesel engines and power solutions to the highest levels of performance and reliability. MARAPCO incorporates this engine throughout their full range.



Leroy Somer is a world leader in the manufacturing of power generation, combining quality with performance to produce a market leading alternator for MARAPCO.



Deep Sea Electronics control modules deliver unrivaled functionality and performance. MARAPCO generating sets use this latest technology to its full potential.

 $Logos\ and\ Brands\ of\ Perkins,\ Leroy\ Somer,\ ABB\ \&\ Deep\ Sea\ Electronics\ \ are\ registered\ Trademarks$ 

Cooling & Lubrication	50Hz		60Hz	
	Liter	US/Gal	Liter	US/Gal
Coolant Capacity:	51.4	13.6	51.4	13.6
Lube Oil Capacity:	40.0	10.6	40.0	10.6
	°C	°F	°C	°F
Exhaust Temperature:	630	1166	660	1220



#### **Other Information**

#### **Generating Set Standards**

This generating set meets the following standards: ISO8528, BS4999, BS5514, IEC60034, VDE0530

#### Warranty

This generator is covered against manufacturing and workmanship defects. Kindly refer to warrant statement for more details.

Picture shown in leaflet may include optional accessories

## Distributed & Serviced by:



JAN2014 VER.1