



Generating Set pictured (open) may include optional accessories

GENERATING SET MODEL (JP2250)

Ratings at 0.8 Power Factor

Output Ratings	Prime	Standby
400-415 V, 3 ph, 50 Hz, 1500 rpm	2250 kVA 1800 kW	2500 kVA 2000 kW

Prime Power These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. 10% overload power is available for 1 hour in 12 hours continuous operation.

Standby Power These ratings are applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings.

STANDARD REFERENCE CONDITIONS

Output ratings are presented at 25°C air inlet temperature, barometric pressure 100 kPa, relative humidity 30%. This generating set is designed to operate at high ambient temperatures (up to 55°C), humidity (up to 99%) and higher altitudes. De-rating may apply, please consult your dealer for specific site ratings.

Some of the specifications are not standard on all Genset models.

ENGINE / TECHNICAL DATA

Engine Make & Model	Perkins 4016-61TRG3	
Governing Class	ISO 8528-5 G2	
Number of Cylinders & Arrangement	16 - 60° Vee	
Bore and Stroke mm	160 x 190	
Displacement / Cubic Capacity litres	61.123	
Induction System	Turbocharged, air to water charge cooled	
Cycle	4 stroke	
Combustion System	Direct Injection	
Compression Ratio	13:1 nominal	
Rotation	Anti-clockwise, viewed from flywheel end	
Cooling System	Water cooled	
Frequency and Engine Speed	50Hz & 1500rpm	
	Prime	Standby
Gross Engine Power kW (hp)	1975 (2647)	2183 (2925)
Fuel Consumption @ 50% load L/hr	234	-
@ 75% load L/hr	344	-
@ 100% load L/hr	470	529
Total Lubrication System Capacity litres	213	213
Total Coolant Capacity (Jacket Water/Secondary Water)	270/230	270/230
Boost Pressure Ratio	4.0	4.0
Exhaust Temperature: °C	475	560
Radiator Cooling Air Flow (Min): m ³ /sec	55.3	55.3
Combustion Air Flow: m ³ /min	160	175
Exhaust Gas Flow: m ³ /min	525	525
Fuel Tank Capacity: litres	NO FUEL TANK	NO FUEL TANK

DIMENSIONS AND WEIGHT (OPEN TYPE)

Length cm	Width cm	Height cm	Weight* kg (wet)
595	219	390	15700

wet weight = with lube oil and coolant

STANDARD SPECIFICATIONS

1. ENGINE

Perkins four stroke heavy duty high performance industrial type diesel engine.

2. ENGINE FILTRATION SYSTEM

- Air filter
- Fuel filter
- Full flow lube oil filter

All filters have replaceable elements.

3. COOLING RADIATOR

Radiator and cooling fan, complete with safety guards, designed to cool the engine at high ambient temperatures (consult your dealer for de-rating factors)

4. EXHAUST SYSTEM

Heavy duty Industrial Exhaust Silencer

Silencer noise reduction level	-
Maximum allowable back pressure	4.0 (kPa)

5. CIRCUIT BREAKER TYPE

3 pole ACB ABB (supplied disconnected and without cables)*

(contd.)

ALTERNATOR DATA

Make	Leroy Somer
Model	LSA52.3L9
No. of bearings	1
Insulation class	H
Total Harmonic Content	<4%
Ingress Protection	IP23
Excitation System	AREP
Winding Pitch	2/3
AVR Model	D510C
Overspeed	2250 mn ⁻¹
Voltage Regulation (steady)	± 0.5%
Short Circuit Capacity	300% (3 In): 10s

PMG Excitation System Available as Optional.

CONTROL PANEL (STANDARD)

Make	Deep Sea
Model	DSE7320

DSE7320 is an Auto Mains (Utility) Failure Control Module. It is operated via the START, STOP, AUTO and MANUAL soft touch membrane buttons on the front panel. DSE7320 can be controlled remotely using either a GSM Modem, Ethernet via DSE860/865 or via RS485.

Protection:

- Fail to start
- Low oil pressure
- High engine temperature
- U/O Voltage shutdown
- U/O Frequency shutdown
- Underspeed, Overspeed
- Loss of engine speed detection
- High/Low battery voltage
- kW overload
- Unbalanced load
- Low fuel alarm (if fitted)
- Battery charger failure (if fitted)

(Please refer to DSE7320 brochure for more details)



JUBAILI BROS IS ISO9001, ISO14001 & OHSAS18001 CERTIFIED



Generating Set pictured (closed) may include optional accessories

SOUND ATTENUATED AND WEATHER PROTECTIVE CONTAINERS - 40' ISO HIGH CUBE CTR

SALIENT FEATURES:

- Lockable external fuel filling point
- Internal /External fuel connection
- External oil drainage
- External coolant drainage
- Air inlet /outlet louvers
- Sound splitters at radiator side (only for 1000 KVA and above) (For 725-880 KVA vertical air discharge)
- Common earth connection
- 2 layers white color paint
- Cooling fan and battery charging alternator fully guarded
- Engine, radiator, fuel fill and battery can only be reached via lockable access doors

CONVENIENT ACCESS FOR MAINTENANCE:

- Original CTR main door as access for operation
- Two doors - one large door on each side (725-880 kVA)
- Two doors in one side and one door in the other side (1000-2500 kVA)
- Lockable doors with emergency opening pusher from inside
- Internal 3-4 lights
- Emergency light on top of the door

TRANSPORTABILITY:

- Lifting points on the top and bottom corners of the containers
- Standard forklift pockets (725-880 kVA)

SOUND PRESSURE LEVEL:

- 80 - 85 dBA at 3 meters (standard)

Customized enclosures with reduced Sound Pressure Levels available on demand

DIMENSIONS AND WEIGHT (CLOSED TYPE)

Length cm	Width cm	Height* cm	Weight kg (wet)	Fuel Tank liter
1200	244	430	27900	NO FUEL TANK

*Excluding 120cm for the silencer on top

AVAILABLE OPTIONS & ACCESSORIES

We offer a range of optional features and accessories to tailor our generating sets to meet your power needs.

OPTIONS

- A variety of generating set control and synchronizing panels
- Additional protection alarms and shutdowns
- Water fuel separator
- Water jacket heater
- Battery charger

ACCESSORIES

- Genuine spare parts
- Load banks
- Auxiliary fuel tanks
- Manual & automatic transfer switches

For further information on all of the standard and optional features accompanying this product please contact your local dealer or visit www.JubailiBros.com
All information in this document is substantially correct at time of printing and may be altered subsequently.

STANDARD SPECIFICATIONS

6. FUEL SYSTEM

On Generating Sets up to 700 KVA, the baseframe design is incorporated with an integral fuel tank with a capacity of approx. 8 hours running at Full Load. The tank is supplied complete with fill cap breather, fuel feed and return lines to the Engine and drain plug.

7. ALTERNATOR

7.1 INSULATION SYSTEM

- The insulation system is Class H.
- All windings are impregnated in either a triple dip thermosetting liquid, oil and acid resisting polyester varnish or vacuum pressure impregnated with a special polyester resin.
- Heavy coat of antitracking varnish additional protection against moisture or condensation.

7.2 AUTOMATIC VOLTAGE REGULATOR (AVR)

The fully sealed Automatic Voltage Regulator maintains the Voltage Regulation at $\pm 1\%$. Nominal adjustment by means of a trim pot incorporated on the AVR.

7.3 MOTOR STARTING

An overload capacity equivalent to 300% of the Full Load impedance at zero Power Factor can be sustained for 10 seconds, when PMG option is fitted.

8. MOUNTING ARRANGEMENT

8.1 BASE FRAME

The complete Generating Set is mounted as a whole on a heavy duty fabricated steel Baseframe.

8.2 COUPLING

The Engine and Alternator are directly coupled by means of an SAE flange. The Engine flywheel is flexibly coupled to the Alternator rotor.

8.3 ANTI-VIBRATION MOUNTING PADS

Anti-Vibration pads are affixed between the Engine / Alternator feet and the Baseframe thus ensuring complete vibration isolation of the rotating assembly.

8.4 SAFETY GUARDS

The Fan & Fan Drive along with the Battery Charging Alternator are Safety Guard protected for personnel protection.

9. FACTORY TESTS

- The Generating set is load tested before dispatch
- All protective devices control functions and site load conditions are simulated. The generator and its systems are checked before dispatch.

10. EQUIPMENT FINISHING

All mild steel components are fully degreased and painted with powder coated paint to ensure maximum scuff resistance and durability.

11. DOCUMENTATIONS

Operation & Maintenance manual, Circuit wiring diagrams and Commissioning / Fault Finding instruction leaflets are accompanied with the Generator.

12. QUALITY STANDARDS

The equipment meets the following standards: BS4999, BS5000, BS5514 IEC 60034, VDE0530, NEMA MG 1.22 and ISO 8528.

13. WARRANTY

All of the Generating Sets are covered under a warranty policy for a period of 12 months. Warranty of the equipment is in line with manufacturers warranty terms & conditions.

(check warranty statement for more details, as it may vary for different countries)

DUBAI

T: +971 4 3242544

F: +971 4 3242545

E: jbdubai@jubailibros.com

ABU DHABI

T: +971 2 5542966

F: +971 2 5541966

E: jb.abudhabi@jubailibros.com

SHARJAH SHOWROOM

T: +971 6 5554605

M: +971 54 5826777

E: jbsarjah@jubailibros.com

JEBEL ALI

T: +971 4 8832023

F: +971 4 8832053

E: jbdubai@jubailibros.com

In line with continuous product development, we reserve the right to change specifications without notice.